



Weight









Benefits:

- For cameras up to 30 x 30mm cross section
- Robust construction
- Compact size and
- Small dead weight
- High IP protection class
- Flexible camera positioning
- High chemical resistance
- Vibration-proof mounting
- Dome and Germanium window option
- Camera mount included
- Excellent heat dissipation
- Custom length option



Technical Details:

Max. Camera Size	30 x 30mm
Max. Lens Diameter	39mm
Inner Length	106mm (XS), 82mm (flat) 146mm (S), 122mm (flat) 176mm (M), 152mm (flat)
Dimensions (w x h) length without cable gland	50 x 50 106mm (XS), 92mm (flat) 146mm (S), 132mm (flat) 186mm (M), 162mm (flat)
Window Aperture	28mm
Standard Window Sapphire Germanium Window Seal	BK7, double sided ARC Order Number: 20.000.041 Order Number: 20.000.094 Hytrel
Protection Class	IP66 (Nema 4)

(incl. camera mount)	Ca. 420g (S), 350g (flat) Ca. 465g (M), 395g (flat)
Enclosure Material	Anodized Aluminum
Enclosure Seals	NBR
Cable Gland Aperture (max. connector size)	20mm (Rear Wall A) 16.5mm (Rear Wall B) 20.5mm (Rear Wall C)
Cable Diameter	4-6.5mm (Rear Wall B)

TPE





Ca 350g (XS) 280g (flat)

4-6.5mm (Rear Wall B) Self drilling (Rear Wall C)

The camera mount guarantees excellent heat dissipation





Cable Gland Seal







Order Numbers:


standard

flat

Product ID	Camera Height	Enclosure Type	Rear Wall/Fro	Length	
2	29 = 2.9 30 = 3.0	0	Front Lid standard 0 Rear Wall 1 Rear Wall 2 Rear Wall	flat A 5 B 6	XS: 080 S: 120 M: 150
Surcharge Colibri Custom Length: 20.000.045			Order separately: Surcha	rge cam mount	Flir Firefly: 20.000.083







Germanium Windows for IR cameras





Special Mount for Flir FireFly

Accessories:

Product	Image	Order No.	Product	Image	Order No.	Product	Image	Order No.
Air Nozzle	4	50.100.023	28mm PA Tube		20.000.006	Mounting Kit 27	Fed	5.270.000
Deflection Mirror 90°	A	20.020.004 + 10.062.979	Mounting Kit 21	61	5.210.000	Mounting Kit 28	100	5.280.000
30/40mm Bracket		10.062.979	Mounting Kit 22	1	5.220.000	Mounting Kit 29	The Is	5.290.000
Surcharge		20.000.092	Mounting Kit 24/24m	LU US	5.240.000 5.240.000m			•



